



247 OLD TAVERN ROAD TEL: 732-938-6333 WEBSITE: [HTTP://WWW.ABMCO.COM](http://www.abmco.com)
HOWELL, NJ 07731 FAX: 732-938-6377 E-MAIL TO [INFO@ABMCO.COM](mailto:info@abmco.com)

MECHANICAL PACKING GASKETS - TEFLON PRODUCTS • FABRICATED RUBBER PARTS • DIE FORMED RINGS

Product Data Sheet Style 8001 & 8002

Description:

Style 8001 is pure graphite tape with adhesive – backed. Style 8002 is pure graphite tape. These ribbons are formed from >95% pure graphite with no impregnates, binders, additives, oils, or greases which could possibly leave the packing and reduce its volume or contaminate the process media. A passive phosphate inhibitor is available by request.

Characteristics:

Packing is easy to install. It is simply wound around the stem or shaft and compressed into place. No special tools are required.

Specifications:

Temperature: -328° F (-200° C) to 932° F (500° C) in oxidizing media; 5432° F (3000° C) continuous in reducing or inert media, 1200° F (650° C) in steam.

pH: 0-14 except strong oxidizers

Construction: Expanded graphite tape, with or without pressure sensitive adhesive or smooth finish.

Sizes:

All thickness can be .015", .010", .005"

¼" x 25'

½" x 25'

¾" x 50'

1" x 50'